



Unità interna			Unità esterne	
				
MSZ-EF22/25/35/42/50VGKB	MSZ-EF22/25/35/42/50VGKS	MSZ-EF18/22/25/35/42/50VGKW	MUZ-EF25/35/42VG	MUZ-EF50VG
Key Technologies				
				
				
				
				
*Optional				

	Capacità nominale kW									
	1.5	1.8	2.0	2.2	2.5	3.5	4.2	5.0	6.0	7.1
Unità interna		•		•	•	•	•	•		
Unità esterna					•	•	•	•		
Multisplit R32					•					

Specifiche tecniche DC INVERTER / POMPA DI CALORE

MODELLO			SET	MSZ-EF18VGK	MSZ-EF22VGK	MSZ-EF25VGK	MSZ-EF35VGK	MSZ-EF42VGK	MSZ-EF50VGK
			Unità interna	MSZ-EF18VGK	MSZ-EF22VGK	MSZ-EF25VGK	MSZ-EF35VGK	MSZ-EF42VGK	MSZ-EF50VGK
			Unità esterna	SOLO MULTISPLIT	SOLO MULTISPLIT	MUZ-EF25VG	MUZ-EF35VG	MUZ-EF42VG	MUZ-EF50VG
Alimentazione	Tensione/Freq./Fasi		V/Hz/n°	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1
	Lato alimentazione			Unità esterna					
Prestazioni Ecodesign EN14825	Raffreddamento	PdesignC	kW	-	-	2,5	3,5	4,2	5,0
		SEER ²		-	-	9,1	8,8	7,9	7,5
		Classe di efficienza energetica	A+++→D	-	-	A+++	A+++	A++	A++
		Consumo energetico annuo ¹	kWh/a	-	-	96	139	186	233
	Riscaldamento Stagione media	Pdesignh	kW	-	-	2,4	2,9	3,8	4,2
		SCOP ³		-	-	4,7	4,6	4,6	4,5
		Classe di efficienza energetica	A+++→D	-	-	A++	A++	A++	A+
		Consumo energetico annuo ¹	kWh/a	-	-	713	882	1151	1304
	Riscaldamento Stagione calda	SCOP ³		-	-	5,9	5,6	6	5,4
		Classe di efficienza energetica	A+++→D	-	-	A+++	A+++	A+++	A+++
Prestazioni EN14511	Raffreddamento	Cap. nominale (min/max)	kW	1,8	2,2	2,5 (0,9 - 3,4)	3,5 (1,1 - 4,0)	4,2 (0,9 - 4,6)	5,0 (1,4 - 5,4)
		Potenza assorbita nominale	kW	-	-	0,54	0,91	1,2	1,55
		EER		-	-	4,63	3,85	3,5	3,23
	Riscaldamento	Cap. nominale (min/max)	kW	2,5	3,0	3,2 (1,0 - 4,2)	4,0 (1,3 - 5,1)	5,4 (1,3 - 6,3)	5,8 (1,4 - 7,5)
		Potenza assorbita nominale	kW	-	-	0,7	0,95	1,455	1,56
		COP		-	-	4,57	4,21	3,71	3,72
Unità interna	Dimensioni	A x L x P	mm	299 x 885 x 195	299 x 885 x 195	299 x 885 x 195	299 x 885 x 195	299 x 885 x 195	299 x 885 x 195
	Peso		kg	11,5	11,5	11,5	11,5	11,5	11,5
	Portata aria	Raffreddamento	m³/min	4-4,6-6,3-8,3-10,5	4-4,6-6,3-8,3-10,5	4-4,6-6,3-8,3-10,5	4-4,6-6,3-8,3-10,5	5,8-6,6-7,7-8,9-11,2	5,8-6,8-7,9-9,2-11,3
		Riscaldamento	m³/min	4-4,6-6,2-8,9-11,9	4-4,6-6,2-8,9-11,9	4-4,6-6,2-8,9-11,9	4-4,6-6,2-8,9-12,7	5,5-6,3-7,8-9,9-13,2	6,4-7,2-9-11,1-14,6
	Pressione sonora (SLo-Lo-Mid-Hi-SHi)	Raffreddamento	dB(A)	21-23-29-36-42	19-23-29-36-42	19-23-29-36-42	21-24-30-36-42	28-31-35-39-43	30-33-36-40-43
		Riscaldamento	dB(A)	21-24-29-37-45	21-24-29-37-45	21-24-29-37-45	21-24-30-38-46	28-30-35-41-48	30-33-37-43-49
Unità esterna	Potenza sonora	Nominale	dB(A)	-	-	60	60	60	60
	Dimensioni	A x L x P	mm	-	-	550 x 800 x 285	550 x 800 x 285	550 x 800 x 285	714 x 800 x 285
	Peso		kg	-	-	31	34	35	40
	Pressione sonora		dB(A)	-	-	47 - 48	49 - 50	50 - 51	52 - 52
Max. corrente assorbita	Potenza sonora	Nominale	dB(A)	-	-	58	62	62	65
			A	-	-	7,1	7,1	10	14
Linee frigorifere	Diametri	Liquido/Gas	mm	6,35 / 9,52	6,35 / 9,52	6,35 / 9,52	6,35 / 9,52	6,35 / 9,52	6,35 / 9,52
	Lunghezza max		m	-	-	20	20	20	30
	Dislivello max		m	-	-	12	12	12	15
Campo funz. garantito	Raffreddamento		°C	-	-	-10 ~ +46	-10 ~ +46	-10 ~ +46	-10 ~ +46
	Riscaldamento		°C	-	-	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24
Refrigerante	Tipo / Precarica		kg	R32 / -	R32 / -	R32 / 0,62	R32 / 0,74	R32 / 0,74	R32 / 1,05
	GWP ² / Tons. Co ₂ Eq.			675 / -	675 / -	675 / 0,42	675 / 0,50	675 / 0,50	675 / 0,71

^{1,2,3} Note di riferimento vedi pag. 64

Accessori	DESCRIZIONE	DURATA	SERIE/OPZ.
MAC-2470FT-E	Filtro purificazione aria V Blocking	12 mesi	Serie